



3M™ PELTOR™ ProTac™ Hunter & ProTac™ Shooter Headset

Product Description

The 3M PELTOR ProTac Hunter and ProTac Shooter Headsets are designed for use whilst hunting and sport shooting. They help protect against harmful impact noise, whilst allowing ambient sounds to be heard at a level below 82dB. They increase your ability to communicate with others nearby, as well as increase your ability to hear approaching game animals.

Key Features

- Attenuating hearing protector
- Level dependent function for ambient listening
- 3.5 mm listen only stereo input (limited to 82 dB) for connection to external devices (e.g. cell phone, two-way radio, Ipad).
- Voice guided menu system
- Auto power off: The headset will turn off after 4 hrs of non-use to save battery
- Low-battery warning at low battery level
- To reduce the corrosion caused by sweat the electronics are located in the outer part of the cup.
- Available in headband version (green)
- Available in two different cup sizes: one with higher attenuation (ProTac Shooter) and one with lower attenuation (ProTac Hunter).

Applications

The 3M PELTOR ProTac Hunter and ProTac Shooter hearing protectors offer a level-dependent function for ambient listening to be used whilst hunting or sport shooting.

Standards and Approvals

3M Svenska AB hereby declares that this 3M™ PELTOR™ Headset is in compliance with the essential requirements and other provisions set out in the appropriate directives. Thereby they fulfil the requirements for CE marking.

The product has been tested and approved in accordance with [EN 352-1:2002, EN352-4:2001/A1:2005, EN 352-6:2002].

Notified Body Statement of Opinion offered by:

PZT GmbH, An der Junkerei 48 F, D-26389 Wilhelmshaven, Germany. Notify body #1974

The product has been tested to AS/NZS 1270:2002 by an independent accredited laboratory.

In the box

- 1 x Headset
- 2 x AA batteries
- 1 x User Instruction

Standard Models

Article number	Description	Legacy 3M ID	SAP ID
MT13H222A	3M™ PELTOR™ ProTac™ Hunter Headset, green, headband	UU004690648	7100088458
MT13H223A	3M™ PELTOR™ ProTac™ Shooter Headset, green, headband	UU004690630	7100088425

Accessories

Article number	Description	Legacy 3M ID	SAP ID
HY220	3M™ PELTOR™ HY220 Hygiene Kit	UU008049353	7100101874
FL6CE/1	3M™ PELTOR™ FL6CE/1 3.5 mm Cable	XH001676952	7000108359
HY100A	3M™ PELTOR™ HY100A CLEAN HYGIENE PAD	XH001651351	7100064410



3M™ PELTOR™ ProTac™ Hunter Headset



Hearing protection with level-dependent function for ambient listening



Hearing protection with external audio input



3M™ PELTOR™ ProTac™ Shooter Headset



Hearing protection with level-dependent function for ambient listening



Hearing protection with external audio input

Technical data specifications

Materials:	Headband (Stainless steel, PVC, PA) Headband wire (stainless steel) Two-point fastener (POM) Cushion (PVC foil and PUR foam) Foam liner (PUR foam) Cup (ABS) Level-dependent Microphone (PUR foam) Latch (PA) On/Off/Mode button (TPE) [+] button (TPE) [-] button (TPE)
Battery type:	2xAA batteries (Alkaline)
Operating time:	Approximately 100 hours of battery lifetime
Net weight (batteries incl.):	ProTac™ Hunter MT13H222A (headband) = 303g ProTac™ Shooter MT13H223A (headband) = 355g
Operating temperature:	-20°C (-4°F) to +55°C (131°F) (battery dependent)
Storage temperature:	-20°C (-4°F) to +55°C (131°F)
Shelf life:	5 years excl. batteries
Wired connectivity:	3.5mm listen-only stereo input jack (limited to 82 dB)

Use limitation: Never modify or alter this product

Attenuation Australia and New Zealand

MT13H222A 3M™ PELTOR™ ProTac™ Hunter Headset AS/NZS 1270:2002

Test Frequency (Hz)	125	250	500	1000	2000	4000	8000	SLC ₉₀	Class	Clamping Force (N)
Mean Attenuation (dB)	13.1	15.7	22.4	28.2	31.8	38.8	35.9	26	5	11
Std. deviation (dB)	3.8	2.1	2.9	2.3	2.4	3.0	4.5			
Mean minus SD	9.3	13.6	19.5	25.9	29.4	35.8	31.4			



MT13H223A 3M™ PELTOR™ ProTac™ Shooter Headset AS/NZS 1270:2002

Test Frequency (Hz)	125	250	500	1000	2000	4000	8000	SLC ₉₀	Class	Clamping Force (N)
Mean Attenuation (dB)	17.6	22.1	29.9	36.4	37.6	38.4	34.9	32	5	11.3
Std. deviation (dB)	3.7	3.7	3.3	2.8	2.2	2.4	2.6			
Mean minus SD	19.9	18.4	26.6	33.6	35.4	36.0	32.3			



3M Personal Safety Division

3M Australia Pty Ltd
Bldg A, 1 Rivett Rd
North Ryde NSW 2113
Customer Service: 1300 363 565
TechAssist Helpline: 1800 024 464
E-mail: techassist@mmm.com.au
Website: www.3M.com/au/PPESafety

3M New Zealand Ltd
94 Apollo Drive, Rosedale
Auckland 0632
Customer Service: 0800 252 627
TechAssist Helpline: 0800 364 357
Website: www.3M.com/nz/PPESafety

Please recycle. Printed in Sweden.
© 3M 2016. All rights reserved.

3M and ProTac are trademarks of 3M Company, used under license in Canada. PELTOR is a trademark of 3M Svenska AB, used under license in Canada.

Warranty

The warranty does not cover any damage caused by neglected maintenance or careless handling.

For more information on maintenance, please see the user instruction.
For complete warranty condition, contact your dealer or local 3M office

Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M.

The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.